

# PHE448


## • Pulse capacitor, polypropylene film/foil

### TYPICAL APPLICATIONS

High frequency and high voltage applications, requiring capacitors with extremely high current handling capability, i.e. high  $dU/dt$  values.

### CONSTRUCTION

Polypropylene film dielectric with aluminum foil and metallized film as electrodes, encapsulated in self-extinguishing material meeting the requirements of UL94V-0.



### GENERAL DATA

Rated voltage  $U_R$ , VDC

Rated voltage  $U_R$ , VAC

Capacitance range, nF

1600	2000
650	700
1.5– 15	0.1– 3.3

p	d	std l	max l	b
$15.0 \pm 0.4$	0.8	$6^{-1}$	30	$\pm 0.4$

Capacitance values

In accordance with E12 series

Capacitance tolerance

$\pm 5\%$  standard.  
Other tolerances on request

Category temperature range

$-55\text{ }^\circ\text{C}$  to  $+105\text{ }^\circ\text{C}$

Rated temperature

$+85\text{ }^\circ\text{C}$

Voltage derating

The rated voltage is decreased with  $1.3\%/^\circ\text{C}$  from  $+85\text{ }^\circ\text{C}$ .

Climatic category

55/105/56

Voltage proof

$2 \times U_R$ , 2s

Insulation resistance

Measured at  $+23\text{ }^\circ\text{C}$ , 100 VDC, 60s  
Between terminals:  
 $\geq 100\ 000\ \text{M}\Omega$   
Between terminals and case:  
 $\geq 100\ 000\ \text{M}\Omega$

Dissipation factor  $\tan\delta$

Max values at  $+23\text{ }^\circ\text{C}$   
1 kHz: 0.03%  
10 kHz: 0.05%  
100 kHz: 0.1%

Pulse rise time

The capacitors can withstand an unlimited number of pulses with a  $dU/dt$  according to the article table.

### ORDERING INFORMATION

The article code for the standard part is given in the article table.  
For other options, see page 12.

### MARKING

- RIFA
- Article code
- Rated capacitance according to IEC 60062
- Capacitance tolerance code
- Rated voltage
- Manufacturing date code (year, month)

### ENVIRONMENTAL TEST DATA

See page 107.

ARTICLE TABLE

Capacitance nF	Box code	Max dimensions in mm			Max dU/dt V/ $\mu$ s	Rthha $^{\circ}$ C/W	Article code
		B	H	L			

Capacitance nF	Box code	Max dimensions in mm			Max dU/dt V/ $\mu$ s	Rthha $^{\circ}$ C/W	Article code
		B	H	L			

1600 VDC/650 VAC

2000 VDC/700 VAC



LEAD SPACING 15 MM

LEAD SPACING 15 MM

1.5	B04	5.5	10.5	18.0	15000	87	PHE448RB4150JR06
1.8	B04	5.5	10.5	18.0	15000	86	PHE448RB4180JR06
2.2	B04	5.5	10.5	18.0	15000	84	PHE448RB4220JR06
2.7	B10	6.5	12.5	18.0	15000	82	PHE448RB4270JR06
3.3	B10	6.5	12.5	18.0	15000	82	PHE448RB4330JR06
3.9	B10	6.5	12.5	18.0	15000	82	PHE448RB4390JR06
4.7	B10	6.5	12.5	18.0	15000	82	PHE448RB4470JR06
5.6	B06	7.5	14.5	18.0	15000	78	PHE448RB4560JR06
6.8	B06	7.5	14.5	18.0	15000	78	PHE448RB4680JR06
8.2	B11	8.5	16.0	18.0	15000	70	PHE448RB4820JR06
10.0	B11	8.5	16.0	18.0	15000	70	PHE448RB5100JR06
12.0	B14	9.5	17.5	18.0	15000	60	PHE448RB5120JR06
15.0	B14	9.5	17.5	18.0	15000	60	PHE448RB5150JR06

0.10	B04	5.5	10.5	18.0	25000	87	PHE448SB3100JR06
0.12	B04	5.5	10.5	18.0	25000	87	PHE448SB3120JR06
0.15	B04	5.5	10.5	18.0	25000	87	PHE448SB3150JR06
0.18	B04	5.5	10.5	18.0	25000	87	PHE448SB3180JR06
0.22	B04	5.5	10.5	18.0	25000	87	PHE448SB3220JR06
0.27	B04	5.5	10.5	18.0	25000	87	PHE448SB3270JR06
0.33	B04	5.5	10.5	18.0	25000	86	PHE448SB3330JR06
0.39	B04	5.5	10.5	18.0	25000	86	PHE448SB3390JR06
0.47	B04	5.5	10.5	18.0	25000	86	PHE448SB3470JR06
0.56	B04	5.5	10.5	18.0	25000	85	PHE448SB3560JR06
0.68	B04	5.5	10.5	18.0	25000	85	PHE448SB3680JR06
0.82	B04	5.5	10.5	18.0	25000	85	PHE448SB3820JR06
1.0	B04	5.5	10.5	18.0	25000	84	PHE448SB4100JR06
1.2	B10	6.5	12.5	18.0	25000	82	PHE448SB4120JR06
1.5	B10	6.5	12.5	18.0	25000	82	PHE448SB4150JR06
1.8	B06	7.5	14.5	18.0	25000	78	PHE448SB4180JR06
2.2	B11	8.5	16.0	18.0	25000	70	PHE448SB4220JR06
2.7	B11	8.5	16.0	18.0	25000	70	PHE448SB4270JR06
3.3	B14	9.5	17.5	18.0	25000	60	PHE448SB4330JR06

DERATING OF  $U_{RMS}$  VS FREQUENCY, +85 $^{\circ}$ C AMBIENT TEMPERATURE AND 10 $^{\circ}$ C INTERNAL HEATING, TYPICAL VALUES



More simulation possibilities in PCCAD. See page 106.